

SECTION 19

GLOSSARY OF TERMS AND ABBREVIATIONS

Absorption. In radio wave propagation, attenuation of a radio wave due to dissipation of its energy, i.e., conversion of its energy into another form, such as heat.

Athermal effect. Any effect of electromagnetic energy on a body that is not a heat-related effect.

Blood–brain barrier. A functional concept developed to explain why many substances that are transported by blood readily enter other tissues but do not enter the brain; the "barrier" functions as if it were a continuous membrane lining the vasculature of the brain. These brain capillary endothelial cells form a nearly continuous barrier to entry of substances into the brain from the vasculature.

Conductance. The reciprocal of resistance. Expressed in siemens (S).

Conductivity: A property of materials that determines the magnitude of the electric current density when an electric field is impressed on the material.

Continuous wave. A wave whose successive oscillations are identical under steady-state conditions.

Current density. A vector of which the integral over a given surface is equal to the current flowing through the surface; the mean density in a linear conductor is equal to the current divided by the cross-sectional area of the conductor. Expressed in ampere per square metre ($A\ m^{-2}$).

Depth of penetration. For a plane wave electromagnetic field (EMF), incident on the boundary of a good conductor, depth of penetration of the wave is the depth at which the field strength of the wave has been reduced to $1/e$, or to approximately 37% of its original value.

Dielectric properties: In the context of this document the properties of materials conductivity and permeability.

Dosimetry. Measurement, or determination by calculation, of internal electric field strength or induced current density, of the specific energy absorption, or specific energy absorption rate distribution, in humans or animals exposed to electromagnetic fields.

Electric field strength. The force (\mathbf{E}) on a stationary unit positive charge at a point in an electric field; measured in volt per metre ($V\ m^{-1}$).

Electrosensitivity (Electrohypersensitivity): A working definition of EHS from Bergqvist et al. (1997) is “a phenomenon where individuals experience adverse health effects while using or being in the vicinity of devices emanating electric, magnetic or electromagnetic fields (EMFs)”.

Electromagnetic energy. The energy stored in an electromagnetic field. Expressed in joule (J).

Electric field strength (E): The magnitude of a field vector at a point that represents the force (F) on a charge (q). E is defined as $E = F/q$ and is expressed in units of Volt per meter (V/m).

Electromagnetic field: Electromagnetic phenomena expressed in vector functions of space and time.

Electromagnetic radiation: The propagation of energy in the form of electromagnetic waves through space.

EMF. Electric, magnetic, and electromagnetic fields.

Exposure: Exposure occurs wherever a person is subjected to electric, magnetic or electromagnetic fields or contact currents other than those originating from physiological processes in the body.

Extra low frequency (ELF): Extra low frequency fields include, in this document, electromagnetic fields from 1 to 300 Hz. Alternately, **ELF-** Extremely low frequency where the European convention is extremely low frequency, US is extra-low frequency.

Frequency modulation (FM): Frequency Modulation is a type of modulation representing information as variations in the frequency of a carrier wave. FM is often used at VHF frequencies (30 to 300 MHz) for broadcasting music and speech.

Far field. The region where the distance from a radiating antenna exceeds the wavelength of the radiated EMF; in the far-field, field components (**E** and **H**) and the direction of propagation are mutually perpendicular, and the shape of the field pattern is independent of the distance from the source at which it is taken.

Frequency. The number of sinusoidal cycles completed by electromagnetic waves in 1 second; usually expressed in hertz (Hz).

Impedance, wave. The ratio of the complex number (vector) representing the transverse electric field at a point to that representing the transverse magnetic field at that point. Expressed in ohm (S).

Magnetic flux density (B): The magnitude of a field vector at a point that results in a

force (F) on a charge (q) moving with the velocity (v). The force F is defined by $F = q*(v \times B)$ and is expressed in units of Tesla (T).

Magnetic field strength (H): The magnitude of a field vector that is equal to the magnetic flux density (B) divided by the permeability (μ) of the medium. H is defined as $H = B/\mu$ and is expressed in units of Ampere per metre (A/m).

Magnetic permeability. The scalar or vector quantity which, when multiplied by the magnetic field strength, yields magnetic flux density; expressed in henry per metre ($H m^{-1}$). *Note:* For isotropic media, magnetic permeability is a scalar; for anisotropic media, it is a tensor quantity.

Microwaves: Microwaves are defined in the frame of this expertise as electromagnetic waves with wavelengths of approximately 30 cm (1 GHz) to 1 mm (300 GHz).

Milligauss (mG)

A milligauss is a measure of ELF intensity and is abbreviated mG. This is used to describe electromagnetic fields from appliances, power lines, interior electrical wiring.

Milliwatt (mW): A unit of power equal to 10^{-3} .

Microwatt (uW): A unit of power equal to 10^{-6}

Microwatts per centimeter squared ($\mu W/cm^2$)

Radiofrequency radiation in terms of power density is measured in microwatts per centimeter squared and abbreviated ($\mu W/cm^2$). It is used when talking about emissions from wireless facilities, and when describing ambient RF in the environment. The amount of allowable RF near a cell tower is 1000 $\mu W/cm^2$ for some cell phone frequencies, for example.

Nanowatt (nW): A unit of power equal to 10^{-9} Watt.

Non – thermal effects (or athermal effects): An effect which can only be explained in terms of mechanisms other than increased molecular motion (i.e. heating), or occurs at absorbed power levels so low, that a thermal mechanism seems unlikely, or displays so unexpected a dependence upon some experimental variable that it is difficult to see how heating could be the cause.

Near field. The region where the distance from a radiating antenna is less than the wavelength of the radiated EMF. *Note:* The magnetic field strength (multiplied by the impedance of space) and the electric field strength are unequal and, at distances less than one-tenth of a wavelength from an antenna, vary inversely as the square or cube of the distance if the antenna is small compared with this distance. Near field exposures are unreliable for estimation of exposures by calculation. They can zero out or be additive and

nearly infinite, thus creating problems for exposure assessment.

Non-ionizing electromagnetic radiation (NIER). Includes all radiations and fields of the electromagnetic spectrum that do not normally have sufficient energy to produce ionization in matter; characterized by energy per photon less than about 12 eV, wavelengths greater than 100 nm, and frequencies lower than 3×10^{15} Hz.

Occupational exposure. All exposure to EMF experienced by individuals in the course of performing their work. Safety limits are five times higher for allowable occupational exposures than for general public exposures in the US.

Permeability (μ): A property of materials that indicates how much polarisation occurs when an electric field is applied.

Permittivity. A constant defining the influence of an isotropic medium on the forces of attraction or repulsion between electrified bodies, and expressed in farad per metre ($F m^{-1}$); *relative permittivity* is the permittivity of a material or medium divided by the permittivity of vacuum.

Public Exposure. All exposure to EMF experienced by the general public excluding exposure during medical procedures and occupational work environments. Public exposure limits in the US are five times lower than for occupational exposures, where informed consent by employees is required.

Power Density. The power as measured in free space (ambient) as opposed to measured by SAR or specific absorption rate (within tissues or the body). The unit of measurement can be watts per square meter, milliwatts per square meter or microwatts per centimeter squared. Radiofrequency (RF). Any frequency at which electromagnetic radiation is useful for telecommunications, or broadcasting for radio and television. Frequency range is usually defined as 300 Hz (300 hertz) to 300 GHz (300 gigahertz).

Radiofrequency (RF): The frequencies between 100 kHz and 300 GHz of the electromagnetic spectrum.

Reasonance. The change in amplitude occurring as the frequency of the wave approaches or coincides with a natural frequency of the medium; whole body absorption of electromagnetic waves presents its highest value, i.e., the resonance. for frequencies (in MHz or megahertz) corresponding to approximately $114/L$ where L is the height of the individual in meters. Reasonance can also be applicable to organs, tissues, or other body parts.

Specific Absorption Rate (SAR is measured in watts per kilogram or W/Kg)

SAR stands for specific absorption rate. It is a calculation of how much RF energy is absorbed into the body, for example when a cell phone or cordless phone is pressed to the head. SAR is expressed in watts per kilogram of tissue (W/Kg). The amount of allowable energy into 1 gram of brain tissue from a cell phone is 1.6 W/Kg in the US. For whole body exposure, the exposure is 0.8 W/Kg averaged over 30 minutes for the general public. International standards in most countries are similar, but not exactly the same.

Static electric field: Static fields produced by fixed potential differences.

Static magnetic fields: Static fields established by permanent magnets and by steady currents.

VDU: Video display units for computers, videos, TV and some measurement devices using cathode ray tubes

WI-FI: Stands for wireless fidelity. WI-FI systems create zones of wireless RF that allow access to wireless internet for computers, internet phone access and other wireless services. Access points that provide WI-FI to access Local Area Networks (LANs) can be installed on streets (for city-wide coverage) or indoors in buildings, Restaurants, hotels, coffee shops, airports, malls and other commercial enterprises are widely installing WI-FI. The range of typical WI-FI systems is about 300 feet.

WI-MAX: Stands for “Wireless interoperability for Microwave Access” and is a telecommunications technology aimed at providing wireless data over long distances. Like WI-FI, WI-MAX systems are designed to provide wireless access but over much broader geographic areas, with some systems transmitting signal up to 10 miles. Higher levels of RF are produced at the wireless transmission facilities than for WI-FI.s

Section 20 LIST OF ABBREVIATIONS

μT	microtesla
μW	microwatt
AC	Alternating current
ALS	Amyotrophic Lateral Sclerosis
AM	Amplitude modulation
B	Magnetic flux density
BBB	Blood-Brain-Barrier
CENELEC	European Committee for Electrotechnical Standardization
CI	Confidence Interval
CNS	Central Nervous System
CW	Continuous wave
DC	Direct current

DECT	Digital Enhanced Cordless Telephone
DMBA	7,12-dimethylbenz[a]anthracene
DNA	Deoxyribonucleic acid
EEG	Electroencephalogram
EHS	Electromagnetic hypersensitivity
ELF	Extra low frequency (also ELF-EMF)
EMF	Electromagnetic field
FM	Frequency Modulation
GSM	Global System for Mobile Communication
H	Magnetic field strength
HSP	Heat-shock proteins (stress proteins)
Hz	Frequency in Hertz
IARC	International Agency for Research on Cancer
IL	Interleukin
kg	Kilogram
kHz	Kilohertz
kV	Kilovolt
MF	Magnetic Field (sometimes MF-ELF)
MHz	Megahertz
ms	Milliseconds
mT	Millitesla
mG	Milligauss
mW	Milliwatt
nT	Nanotesla
nW	Nanowatt
NRPB	National Radiation Protection Board (HPA)
OR	Odds Ratio (measure of increased risk of disease)
REFLEX	European Research Program for Radiofrequency Hazards
RF	Radiofrequency Radiation (also written as RFR or RF-EMF)
SCENIHR	Scientific Committee on Emerging and Newly Identified Health Risks
TNO	Nederlandse Onderzoek (Netherlands Organisation Applied Scientific Research
UMTS	Universal Mobile Telephony System
UNEP	United Nations Environmental
VDT	Video display terminal (VDU – for computers, videos, TV, that use cathode ray tubes).
Wi-Fi	Short for wireless fidelity – wireless internet access - works for short-distances for cell phone and laptop computer access without wires.
WLAN	Wireless Local Area Network (wireless internet coverage usually up to 300'

provided by access points that create elevated radiofrequency radiation for that service zone.

- WiMAX** Worldwide Interoperability for Microwave Access (wireless service up to 10 miles in comparison to Wi-Fi that may serve 300' area)
- WHO** World Health Organisation
- FCC** The Federal Communications Commission (FCC) is an independent United States government agency, created, directed, and empowered by Congressional statute to oversee the regulation of radio and TV broadcasting and wireless technologies. It is not a health agency.
- HPA** Health Protection Agency (UK) that was formerly the National Radiation Protection Division Board). The Health Protection Agency (HPA) is an independent body that protects the health and well-being of the population. The Agency plays a critical role in protecting people from infectious diseases and in preventing harm when hazards involving chemicals, poisons or radiation occur.
- DNA** Deoxyribonucleic acid, or DNA is a nucleic acid molecule that contains the genetic instructions used in the development and functioning of all living things.
- Melatonin** Melatonin is a hormone produced in the brain by the pineal gland, It is a potent anti-oxidant that protects against oxidative damage from free radicals that can cause DNA damage.
- Alzheimer's** Alzheimer's disease is a progressive brain disorder that gradually destroys a person's memory and ability to learn, reason, make judgments, communicate and carry out daily activities. As Alzheimer's progresses, individuals may also experience changes in personality and behavior, such as anxiety, suspiciousness or agitation, as well as delusions or hallucinations.
- RFAIWG** Radiofrequency Interagency Working Group (US) composed of members from federal agencies with some interest in radiofrequency radiation issues. This Working Group was made up of representatives from the US government's National Institute for Occupational Safety and Health (NIOSH), the Federal Communications Commission (FCC), Occupational Health and Safety Administration (OSHA), the Environmental Protection Agency (US EPA), the National Telecommunication and Information Administration, and the US Food and Drug Administration (FDA).
- ICNIRP** International Commission on Non-Ionizing Radiation. It is a body of independent scientific experts consisting of a main Commission of 14 members, 4 Scientific Standing Committees covering Epidemiology, Biology, Dosimetry and Optical Radiation and a number of consulting

experts. This expertise is brought to bear on addressing the important issues of possible adverse effects on human health of exposure to non-ionising radiation.